

Envirosense™ Power Direct Vent

96% Efficient

Power Direct-Vent Residential Gas Water Heater

The 100,000 BTU Envirosense™ Power Direct Vent residential gas water heater is equipped with a fully submerged, spiral-shaped condensing heat exchanger and 50 gallons of storage capacity. This design provides much greater heat transfer surface than a standard straight flue tube, resulting in 96% thermal efficiency and higher hot water output than comparable 80% efficient water heaters. It can deliver a continuous flow of over 4.0 gallons per minute.* With a 22" diameter, the Envirosense™ Power Direct Vent can be installed in less space than a 75-gallon unit yet delivers greater recovery and lower operating costs.

Power Direct-Vent Design for Installation Versatility

- Modular blower, with 120V, 60Hz electrical system (5 amps or less)
- Combined horizontal and vertical vent runs terminating through outside wall, using Schedule 40 PVC pipe as follows:
 - 2" pipe allows vent runs up to 45 equivalent feet
 - 3" pipe allows vent runs up to 128 equivalent feet

Available in Natural Gas or Propane

Side-Mounted Taps for Recirculating Systems

- Hot and cold "side taps" allow the Envirosense™ Power Direct Vent to be used for "combination" systems for water heating plus space heating, radiant floor heating or other applications requiring a recirculating hot water loop
- Plugs for recirculating taps are factory installed

Advanced Electronic Control

- Large LCD display
- Precise temperature control
- Advanced diagnostics

Glass Lined Tank with Two Magnesium Anode Rods

- Provides superior protection against corrosion
- Commercial-grade glass lining protects all "water side" tank surfaces plus inside of internal heat exchanger exposed to condensate

Top-Fired Low-NOx Burner

- Reduces NOx emissions up to 33% and complies with requirements for NOx emissions of 40 ng/J or less

Factory-Installed Temperature and Pressure Relief Valve

Maximum Hydrostatic Working Pressure: 150 psi

Meets ASHRAE/IESNA 90.1 (latest standard)

- Design-certified by Underwriters Laboratories (UL) according to ANSI Z21.10.3-CSA4.3 standards governing storage-type water heaters

Six-Year Limited Parts And Tank Warranty

- Consult written warranty shipped with water heater or contact Reliance for complete warranty information

* 4.3 GPM continuous flow, based on 65°F inlet water temperature and 110°F outlet water temperature.



Envirosense™ Power Direct Vent

96% Efficient

Power Direct-Vent Residential Gas Water Heater

SPECIFICATIONS



MODEL NUMBER	BTU INPUT PER HOUR	TANK SIZE GALLONS	FIRST HOUR DELIVERY GALLONS	RECOVERY-GALLONS PER HOUR AT 90F RISE	SHIPPING WEIGHT LBS.
6 50 YTPDT	100,000	50	164	129	255

Manifold Pressure: 4.0 inches w.c. (.99 kPa); All models—Maximum Supply Pressure: 14 inches w.c. (3.48 kPa) Minimum Supply Pressure Natural Gas: 3.5 inches w.c. (.87 kPa). Minimum Pressure Propane: 8.0 inches w.c. (1.99 kPa). Minimum Pressure must be maintained under both load and no-load (static and dynamic) conditions.

DIMENSIONS


6 50 YTPDT	A	B	C	D	E	F
INCHES	66-3/4	49-1/4	22	15-3/4	3	8

Top inlet and outlet: 3/4" male NPT
Side inlet and outlet: 3/4" female NPT
Gas inlet: 1/2" NPT



*INSTALL IN ACCORDANCE WITH LOCAL CODES.

Optional Concentric Vent Kit Part # 9006328005



SUGGESTED SPECIFICATION

(Natural or Propane) gas water heater(s) shall be EnviroSense™ Power Direct Vent model # 6 50 YPDT, with 96% thermal efficiency, a storage capacity of 50 gallons, an input rating of 100,000 BTU per hour, a recovery rating of 129 gallons per hour at 90°F rise and a maximum hydrostatic working pressure of 150 psi. Water heater(s) shall be of power direct-vent design, using 2", 3" or 4" PVC pipe for horizontal and or vertical vent runs. Water heater(s) shall have: 1: Seamless, glass lined steel tank construction and a spiral-shaped heat exchanger placed entirely inside the tank, which shall be glass lined on the flue gas side to protect against acidic condensate. 2: Advanced electronic control with large LCD display and advanced diagnostics. 3: A 6-year limited warranty on parts and tank. Water heater(s) shall meet or exceed ASHRAE/IESNA 90.1 (latest revision), and be design-certified by UL (Underwriters Laboratories) according to ANSI Z21.10.3-CSA4.3 standards governing storage tank water heaters.

For complete information on limited warranties, consult written warranty or contact the Reliance® Customer Care Center at 1-800-365-4054. Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice.

For more information, contact:
Reliance® Water Heater Company
500 Tennessee Waltz Parkway
Ashland City, TN 37015
800-365-4054 Toll-free USA
www.reliancewaterheaters.com

Reliance Water Heaters