

NON-CONDENSING GAS TANKLESS WATER HEATERS

NON-CONDENSING GAS TANKLESS with X3® SCALE PREVENTION

Dependable hot water is available for all with Reliance® non-condensing gas tankless water heaters. They deliver on-demand performance, reliability and the flexibility to install in practically any residential setting, indoor or out.

- **X3® Scale Prevention Technology**
 - Integrated into all X3 models
 - Eliminates the need for regular scale-related maintenance
 - Maintains “like-new” performance longer, extends life up to 3x longer
- **15-Year Limited Warranty (X3 models), 10-Year Limited Warranty (Base models), on heat exchanger**
5-Year Limited Warranty on all parts
No hardwater exclusions on X3 models, exclusions apply to Base (B) models
- **Ease of Installation:**
 - Indoor or Outdoor models
 - Wi-Fi connectivity with optional kit
 - 3/4” gas line or larger
 - Pressure relief valve on X3 models
 - Outdoor power rated cord standard
 - Manufactured Home approved
 - Cascade up to 12 units with single cable per heater, cable included
 - Concentric (Direct Vent) - Indoor
- **Ultra-Low NOx emissions***

MORE FEATURES ON BACK

*Ultra Low NOx – Complies with SCAQMD Rule 1146.2 and other air quality management districts with similar NG NOx emission requirements of 14 ng/J or 20 ppm at 3% O₂.



Left:
X3 Outdoor Model
ATO-180X3, ATO-199X3
with Integrated X3 Scale
Prevention Technology

Right:
X3 Indoor Model
ATI-180X3, ATI-199X3
with Integrated X3 Scale
Prevention Technology

Bottom:
Base Indoor Model
ATI-180B, ATI-199B

Base Outdoor Model also
available





EASY-TO-USE ELECTRONIC DISPLAY

- User Friendly, Easy to Read
- Display features:
 - On/Off button
 - Temperature Setting button
 - Status Codes
 - Error Codes

MORE FEATURES (continued from front)

■ Performance & Efficiency

- 180,000, 199,000 BTU/h
- 10,000 BTU min. input
- Max Flow Rate 10.5 GPM; 0.4 GPM activation;
0.26 GPM for continuous fire
- 0.82 UEF
- Ultra Low NOx – Complies with SCAQMD Rule 1146.2*

*Ultra Low NOx – Complies with SCAQMD Rule 1146.2 and other air quality management districts with similar NG NOx emission requirements of 14 ng/J or 20 ppm at 3% O₂.

NON-CONDENSING GAS TANKLESS - X3® and BASE MODELS

| Model Number | Installation Type | Gas Consumption Input (BTU/Hour) | | UEF | Maximum GPM** | Dimensions | | | |
|--------------------|-------------------|----------------------------------|---------|------|---------------|------------|---------|---------|--------|
| | | Minimum | Maximum | | | Height*** | Width | Depth | Weight |
| X3® MODELS | | | | | | | | | |
| RTI-199X3-N | Indoor | 10,000 | 199,000 | 0.82 | 10.5 | 36 7/8" | 15 1/2" | 10 3/4" | 65 lb. |
| RTI-180X3-N | | | 180,000 | | 10.0 | | | | |
| RTO-199X3-N | Outdoor | 10,000 | 199,000 | 0.82 | 10.5 | 34 1/2" | 15 1/2" | 11 1/4" | 65 lb. |
| RTO-180X3-N | | | 180,000 | | 10.0 | | | | |
| BASE MODELS | | | | | | | | | |
| RTI-199B-N | Indoor | 10,000 | 199,000 | 0.82 | 10.5 | 28" | 15 1/2" | 10 3/4" | 65 lb. |
| RTI-180B-N | | | 180,000 | | 10.0 | | | | |
| RTO-199B-N | Outdoor | 10,000 | 199,000 | 0.82 | 10.5 | 25 1/2" | 15 1/2" | 11 1/4" | 65 lb. |
| RTO-180B-N | | | 180,000 | | 10.0 | | | | |

** Current numbers based on factory settings

***Height with integrated X3 Scale Control Media cartridge installed.

Included with Heater: Manual, Pressure Relief Valve (X3 models only), Wall Mounting Bracket and Hardware, Vent Port Screws, Cascading Cable, Bird Screens

For complete information consult written warranty.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.



Reliance Water Heaters

RELIANCE® WATER HEATERS

www.ReliaceWaterHeaters.com
500 Tennessee Waltz Pkwy., Ashland City, TN 37015, 1-800-365-4054

©2026 Reliance Water Heaters. All rights reserved.
RGTNCS0526

